

Low Pressure Reusable Coupling

The Exitflex Reusable fittings are made of 2 pieces. The nut, the stainless steel insert and the ferrule.

Type Ref	Connection Bore	Hose	For Hose Type
76-221/39	1/4 NPSM (F)	3/16	LX1.3
76-222/39	1/4 BSP (F)	3/16	LX1.3
76-236/39	M16x1.5 (F)	3/16	LX1.3
76-238/39	3/8 NPSM (F)	3/16	LX1.3
76-239/39	3/8 BSP (F)	3/16	LX1.3
76-341/39	1/4 NPSM (F)	1/4	LM, MA, MF, MO & RPUA1.4
76-342/39	1/4 BSP (F)	1/4	as above
76-343/39	M14 x 1 (F)	1/4	as above
76-358/39	3/8 NPSM (F)	1/4	as above
76-359/39	3/8 BSP (F)	1/4	as above
76-303/31	Spring guard	300 series body (above)	
76-441/39	1/4 NPSM (F)	1/4	AL, LPC & LPV1.4
76-442/39	1/4 BSP (F)	1/4	as above
76-458/39	3/8 NPSM (F)	1/4	as above
76-459/39	3/8 BSP (F)	1/4	as above
76-561/39	1/4 NPSM (F)	5/16	as above
76-562/39	1/4 BSP (F)	5/16	as above
76-511/39	1/4 NPSM (F)	5/16	AL, RA, LPC & LPV1.5
76-512/39	1/4 BSP (F)	5/16	as above
76-570/6	1/4 BSP (M)	5/16	as above
76-578/39	3/8 NPSM (F)	5/16	as above
76-579/39	3/8 BSP (F)	5/16	as above
76-688/39	3/8 NPSM (F)	3/8	AB, LPC LPV1.6
76-689/39	3/8 BSP (F)	3/8	as above
76-691/39	1/4 NPSM (F)	3/8	as above
76-692/39	1/4 BSP (F)	3/8	as above
76-761/39	1/4 NPSM (F)	5/16	MA, MO, RPUA LM & LMC1.5
76-762/39	1/4 BSP (F)	5/16	as above
76-778/39	3/8 NPSM (F)	5/16	as above
76-779/39	3/8 BSP (F)	5/16	as above
76-888/39	3/8 NPSM (F)	3/8	MA, MO & RPUA1.6
76-889/39	3/8 BSP (F)	3/8	as above
76-891/39	1/4 NPSM (F)	3/8	as above
76-892/39	1/4 BSP (F)	3/8	as above

